Product Specification
01/07/2021

EvoTorque 2 ET2-119-6000-230

Part number: 180225.B12
EAN Bar Code: 5060207568029
NATO number: -
Accuracy: ±3%
Operates between:
600.00 - 6000.00 N·m
443.00 - 4500.00 lbf·ft

TECHNICAL SPECIFICATIONS

- 1 1/2" Square Drive
- 3.3 rpm
- Tool Weight of 16.8kg
- Calibrated to 20% - 100% of tool's maximum capacity
- Operational targets can be set from 10% of tool capacity
- 230V: 0

FEATURES

- 'Usage' counter gives the ability to see the amount of times the tool has been used since the last reset
- "Operation Direction" designed primarily for undoing bolts. When doing sequence tightening, it is now possible to undo an incorrectly tightened bolt without interrupting the sequence
- 2 Stage Tightening gives faster application of a Snug Torque & Angle Target
- "Turn Angle" option can be used to check if bolts have already been tightened in an assembly process
- Allows tool integration into third party control systems
- Maximum Audit Mode target angle increased to 720 degrees
- Ability to produce and store real time graphs via EvoLog
- 2 different lock levels, lock level 1 as per previous lock, lock level 2 will not allow user to exit the run screen or change the target
- Torque, Torque & Angle, Torque & Angle with Final Torque or Torque Audit Modes
- Each tool is supplied with a traceable calibration certificate
- For more features please see link to sales leaflet under catalogue below

NORBAR TORQUE TOOLS LTD. Wildmere Road, Banbury, Oxfordshire, OX16 3JU, United Kingdom
Registered Office as above - Registered in England No. 380480 - VAT No. GB 119 1060 05

- Tel: + 44 (0) 1295 270333
- Enquiries: + 44 (0) 1295 753600
- After Sales : + 44 (0) 1295 753635
- Fax: + 44 (0) 1295 753609
- Email: enquiry@norbar.com
- Repairs: repairs@norbar.com