

PneuTorque PTS Remote, 200 - 1000 N·m, 147 - 738 lbf·ft



Remote control versions have no direction control on the tool but rely on external pneumatic circuitry to provide this function. This opens up numerous application possibilities for the PneuTorque® ranging from simple stall shut-off in a hazardous working environment to sophisticated, multi-spindle torque and angle shut-off systems.

PTS™ Remote tools are supplied without reaction, click [here](#) to see the reaction range or contact us directly to discuss bespoke engineered options

Part number: 180273.B06

EAN Bar Code: 5060207568357

NATO number: -

Accuracy: ±3%

Operates between:

200.00 - 1000.00 N·m

147.00 - 738.00 lbf·ft



TECHNICAL SPECIFICATIONS

- Length: 311mm
- Weight: 6.14kg
- Square Drive: 3/4"
- Output Speed (rpm): 16

FEATURES

- Designed to offer excellent power-to-weight ratio
- Replaceable square drive
- ±3% repeatability of reading from 20% to 100% of range
- Supplied as standard with a traceable calibration certificate in a clockwise direction only

NORBAR TORQUE TOOLS LTD. Wildmere Road, Banbury, Oxfordshire,
OX16 3JU, United Kingdom
Registered Office as above - Registered in England No. 380480 - VAT No.
GB 119 1060 05

- Tel: + 44 (0) 1295 270333
- Enquiries: + 44 (0) 1295 753600
- After Sales : + 44 (0) 1295 753635
- Fax: + 44 (0) 1295 753609
- Email: enquiry@norbar.com
- Repairs: repairs@norbar.com